



DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY	MISURE DI INGOMBRO OVERALL DIMENSIONS		
L x H	Z x HT	P	LT
600+600 x 2000/2030/2100	2000 x 2100/2130/2200	655	650
650+650 x 2000/2030/2100	2150 x 2100/2130/2200	705	700
700+700 x 2000/2030/2100	2300 x 2100/2130/2200	755	750
750+750 x 2000/2030/2100	2450 x 2100/2130/2200	805	800
800+800 x 2000/2030/2100	2600 x 2100/2130/2200	855	850
850+850 x 2000/2030/2100	2750 x 2100/2130/2200	905	900
900+900 x 2000/2030/2100	2900 x 2100/2130/2200	955	950
950+950 x 2000/2030/2100	3050 x 2100/2130/2200	1005	1000
1000+1000 x 2000/2030/2100	3200 x 2100/2130/2200	1055	1050
1100+1100 x 2000/2030/2100	3500 x 2100/2130/2200	1155	1150
1200+1200 x 2000/2030/2100	3800 x 2100/2130/2200	1255	1250

PANNELLO PORTA (LEGNO) DOOR PANEL (WOOD)	
LP	HP
615 ÷ 630	2010/2040/2110
665 ÷ 680	2010/2040/2110
715 ÷ 730	2010/2040/2110
765 ÷ 780	2010/2040/2110
815 ÷ 830	2010/2040/2110
865 ÷ 880	2010/2040/2110
915 ÷ 930	2010/2040/2110
965 ÷ 980	2010/2040/2110
1015 ÷ 1030	2010/2040/2110
1115 ÷ 1130	2010/2040/2110
1215 ÷ 1230	2010/2040/2110

PARETE FINITA - FINISHED WALL					
	175	200	230		
H	500 ÷ 2300	500 ÷ 2600	2650 ÷ 3000	500 ÷ 2600	2650 ÷ 3000
SI	55	67	59	80	62

NOTE TECNICHE - TECHNICAL NOTES

- Realizzazione dei controtelai con intervalli in altezza e larghezza ogni 50 mm.
- Per sede interna (SI) da 55 mm è consigliabile pannelli porta con SP max 40 mm, comprese eventuali cornici fermavetro.
- Dimensioni disponibili a richiesta: L= 300 + 300 mm ÷ 1500 + 1500 mm e H= 500 ÷ 3000 mm.
- Per misure speciali verificare fattibilità in azienda.
- Portata standard dei carrelli 150 Kg. • In fase d'ordine si prega di specificare la tipologia (A o B).
- Realization of the pocket frames with a pitch in height and width every 50 mm.
- For pocket frames with internal opening (SI) of 55 mm, it is advisable to install a door panel with a max. thickness of 40 mm, including any frames for glass.
- Dimensions available on request: L= 300 + 300 mm ÷ 1500 + 1500 mm and H= 500 ÷ 3000 mm.
- For special dimensions, please check the feasibility with the company.
- Standard payload of the supplied hanging kit 150 Kg. • When ordering, please specify the type (A or B).