



DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY	MISURE DI INGOMBRO OVERALL DIMENSIONS	PANNELLO PORTA (LEGNO) DOOR PANEL (WOOD)					
		L x H	Z x HT	P	LT	LP1	HP1
1200 (300x4) x 2000/2100	1930 x 2120/2220	1250	340	340	1990/2090	300	1987/2087
1400 (350x4) x 2000/2100	2230 x 2120/2220	1450	390	390	1990/2090	350	1987/2087
1600(400x4) x 2000/2100	2530 x 2120/2220	1650	440	440	1990/2090	400	1987/2087
1800(450x4) x 2000/2100	2830 x 2120/2220	1850	490	490	1990/2090	450	1987/2087
2000 (500x4) x 2000/2100	3130 x 2120/2220	2050	540	540	1990/2090	500	1987/2087
2200 (550x4) x 2000/2100	3430 x 2120/2220	2250	590	590	1990/2090	550	1987/2087
2400 (600x4) x 2000/2100	3730 x 2120/2220	2450	640	640	1990/2090	600	1987/2087

	PARETE FINITA - FINISHED WALL		
	150	174	200
H	2000/2100	2000/2100	2000/2100
SI	112	136	162
O	125	-	-

### NOTE TECNICHE - TECHNICAL NOTES

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm.
- La luce nominale (L) è ridotta di circa 20 mm.
- Per sede interna (SI) da 112 mm è consigliabile installare pannello porta con SP max 40 mm, comprese eventuali cornici fermavetro.
- Per il fissaggio delle lastre di cartongesso utilizzare viti L max 19 mm in corrispondenza delle doghe di rinforzo della lamiera.
- Si consiglia l'utilizzo di lastre in cartongesso di 12,5 mm di spessore.
- Per misure speciali verificare fattibilità in azienda.
- Portata standard dei carrelli 150 Kg.
- Creation of pocket frames with height and width intervals every 50 mm.
- The doorway (L) is reduced by an approximate 20 mm.
- For pocket frames with internal opening (SI) of 112 mm, it is advisable to install a door panel with a max. thickness of 40 mm, including any frames for glass.
- To fasten the plasterboard sheets, use screws of max. 19 mm in correspondence with the reinforcement slats of the sheet.
- The use of 12.5 mm thick plasterboard sheets is recommended.
- For special dimensions, please check the feasibility with the company.
- Standard payload of the supplied hanging kit 150 Kg.