



DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY		MISURE DI INGOMBRO OVERALL DIMENSIONS		PANNELLO PORTA (LEGNO) DOOR PANEL (WOOD)				
L x H		Z x HT	P	LT	LP1	HP1	LP2	HP2
1200 (300x4) x 2000/2100		1930 x 2120/2220	1250	340	340	1990/2090	300	1987/2087
1400 (350x4) x 2000/2100		2230 x 2120/2220	1450	390	390	1990/2090	350	1987/2087
1600 (400x4) x 2000/2100		2530 x 2120/2220	1650	440	440	1990/2090	400	1987/2087
1800 (450x4) x 2000/2100		2830 x 2120/2220	1850	490	490	1990/2090	450	1987/2087
2000 (500x4) x 2000/2100		3130 x 2120/2220	2050	540	540	1990/2090	500	1987/2087
2200 (550x4) x 2000/2100		3430 x 2120/2220	2250	590	590	1990/2090	550	1987/2087
2400 (600x4) x 2000/2100		3730 x 2120/2220	2450	640	640	1990/2090	600	1987/2087

PARETE FINITA - FINISHED WALL			
	150	174	200
H	2000/2100	2000/2100	2000/2100
SI	112	136	162
TR	120	-	-

NOTE TECNICHE - TECHNICAL NOTES

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm.
- La luce nominale (L) è ridotta di circa 20 mm.
- Per sede interna (SI) da 112 mm è consigliabile pannello porta con SP max 40 mm, comprese eventuali cornici fermavetro.
- Per misure speciali verificare fattibilità in azienda.
- Portata standard dei carrelli 150 Kg.
- Creation of pocket frames with height and width intervals every 50 mm.
- The doorway (L) is reduced by an approximate 20 mm.
- For pocket frames with internal opening (SI) of 112 mm, it is advisable to install a door panel with a max. thickness of 40 mm, including any frames for glass.
- For special dimensions, please check the feasibility with the company.
- Standard payload of the supplied hanging kit 150 Kg.