



DIMENSIONI STANDARD - STANDARD DIMENSIONS

| LUCE DI PASSAGGIO<br>DOORWAY |  | MISURE DI INGOMBRO<br>OVERALL DIMENSIONS |  | PANNELLO PORTA (LEGNO)<br>DOOR PANEL (WOOD) |     |     |           |     |           |
|------------------------------|--|--|--|---|-----|-----|-----------|-----|-----------|
| L x H                        |  | Z x HT                                   |  | P   | LT  | LP1 | HP1       | LP2 | HP2       |
| 600 (300x2) x 2000/2100      |  | 1030 x 2100/2200                         |  | 665   | 340 | 340 | 1990/2090 | 300 | 1987/2087 |
| 700 (350x2) x 2000/2100      |  | 1180 x 2100/2200                         |  | 765   | 390 | 390 | 1990/2090 | 350 | 1987/2087 |
| 800 (400x2) x 2000/2100      |  | 1330 x 2100/2200                         |  | 865   | 440 | 440 | 1990/2090 | 400 | 1987/2087 |
| 900 (450x2) x 2000/2100      |  | 1480 x 2100/2200                         |  | 965   | 490 | 490 | 1990/2090 | 450 | 1987/2087 |
| 1000 (500x2) x 2000/2100     |  | 1630 x 2100/2200                         |  | 1065  | 540 | 540 | 1990/2090 | 500 | 1987/2087 |
| 1100 (550x2) x 2000/2100     |  | 1780 x 2100/2200                         |  | 1165  | 590 | 590 | 1990/2090 | 550 | 1987/2087 |
| 1200 (600x2) x 2000/2100     |  | 1930 x 2100/2200                         |  | 1265  | 640 | 640 | 1990/2090 | 600 | 1987/2087 |

| PARETE FINITA - FINISHED WALL |           |           |           |
|-------------------------------|-----------|-----------|-----------|
|                               | 150       | 174       | 200       |
| H                             | 2000/2100 | 2000/2100 | 2000/2100 |
| SI                            | 112       | 136       | 162       |
| O                             | 125       | -         | -         |

### NOTE TECNICHE - TECHNICAL NOTES

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm. • La luce nominale (L) è ridotta di circa 10 mm.
- Per sede interna (SI) da 112 mm è consigliabile pannello porta con SP max 40 mm, comprese eventuali cornici fermavetro.
- Per il fissaggio delle lastre di cartongesso utilizzare viti L max 19 mm in corrispondenza delle doghe di rinforzo della lamiera.
- Si consiglia l'utilizzo di lastre in cartongesso di 12,5 mm di spessore. • Per misure speciali verificare fattibilità in azienda.
- Portata standard dei carrelli 150 Kg.

- Creation of pocket frames with height and width intervals every 50 mm. • The doorway (L) is reduced by an approximate 10 mm.
- For pocket frames with internal opening (SI) of 112 mm, it is advisable to install a door panel with a max. thickness of 40 mm, including any frames for glass.
- To fasten the plasterboard sheets, use screws of max. 19 mm in correspondence with the reinforcement slats of the sheet.
- The use of 12.5 mm thick plasterboard sheets is recommended. • For special dimensions, please check the feasibility with the company.
- Standard payload of the supplied hanging kit 150 Kg.