



DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY	MISURE DI INGOMBRO OVERALL DIMENSIONS	P	LT
L x H	Z x HT	P	LT
600 (300x2) x 2000/2100	1030 x 2100/2200	665	340
700 (350x2) x 2000/2100	1180 x 2100/2200	765	390
800 (400x2) x 2000/2100	1330 x 2100/2200	865	440
900 (450x2) x 2000/2100	1480 x 2100/2200	965	490
1000 (500x2) x 2000/2100	1630 x 2100/2200	1065	540
1100 (550x2) x 2000/2100	1780 x 2100/2200	1165	590
1200 (600x2) x 2000/2100	1930 x 2100/2200	1265	640

PANNELLO PORTA (LEGNO) DOOR PANEL (WOOD)			
LP1	HP1	LP2	HP2
340	1990/2090	300	1987/2087
390	1990/2090	350	1987/2087
440	1990/2090	400	1987/2087
490	1990/2090	450	1987/2087
540	1990/2090	500	1987/2087
590	1990/2090	550	1987/2087
640	1990/2090	600	1987/2087

PARETE FINITA - FINISHED WALL			
	150	174	200
H	2000/2100	2000/2100	2000/2100
SI	112	136	162
TR	120	-	-

NOTE TECNICHE - TECHNICAL NOTES

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm.
- La luce nominale (L) è ridotta di circa 10 mm.**
- Per sede interna (SI) da 112 mm è consigliabile pannello porta con SP max 40 mm, comprese eventuali cornici fermavetro.
- Per misure speciali verificare fattibilità in azienda.
- Portata standard dei carrelli 150 Kg.
- Creazione di pocket frames with height and width intervals every 50 mm.
- The doorway (L) is reduced by an approximate 10 mm.**
- For pocket frames with internal opening (SI) of 112 mm, it is advisable to install a door panel with a max. thickness of 40 mm, including any frames for glass.
- For special dimensions, please check the feasibility with the company.
- Standard payload of the supplied hanging kit 150 Kg.