



**DIMENSIONI STANDARD - STANDARD DIMENSIONS**

LUCE DI PASSAGGIO DOORWAY		MISURE DI INGOMBRO OVERALL DIMENSIONS		PANNELLO PORTA (LEGNO) DOOR PANEL (WOOD)			
L x H	Z x HT	P	LT	LP1	HP1	LP2	HP2
1200 (300x4) x 2000/2100	1930 x 2100/2200	1250	340	340	1990/2090	300	1987/2087
1400 (350x4) x 2000/2100	2230 x 2100/2200	1450	390	390	1990/2090	350	1987/2087
1600 (400x4) x 2000/2100	2530 x 2100/2200	1650	440	440	1990/2090	400	1987/2087
1800 (450x4) x 2000/2100	2830 x 2100/2200	1850	490	490	1990/2090	450	1987/2087
2000 (500x4) x 2000/2100	3130 x 2100/2200	2050	540	540	1990/2090	500	1987/2087
2200 (550x4) x 2000/2100	3430 x 2100/2200	2250	590	590	1990/2090	550	1987/2087
2400 (600x4) x 2000/2100	3730 x 2100/2200	2450	640	640	1990/2090	600	1987/2087

PARETE FINITA - FINISHED WALL						
	100	125	150	150#		
	100 lastra singola / single sheet 125 lastra doppia / double sheet	125 lastra singola / single sheet 150 lastra doppia / double sheet	150 lastra singola / single sheet	150 lastra singola / single sheet		
H	2000/2100	2000/2100	2000/2100	2000/2100		
SI	55	80	105	52		
O	75	100	125	70		

# Realizzata con orditura da 70 mm. - Made with a 70 mm profile for plasterboard.

**NOTE TECNICHE - TECHNICAL NOTES**

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm. • La luce nominale (L) è ridotta di circa 100 mm.
- Per sedè interna (SI) da 52 o da 55 mm è consigliabile pannello porta con SP max 40 mm, comprese eventuali cornici fermavetro.
- Per il fissaggio delle lastre di cartongesso utilizzare viti L max 19mm in corrispondenza delle doghe di rinforzo della lamiera.
- Si consiglia l'utilizzo di lastre in cartongesso di 12,5 mm di spessore. • Per misure speciali verificare fattibilità in azienda.
- Portata standard dei carrelli 150 Kg.

- Creation of pocket frames with height and width intervals every 50 mm. • The doorway (L) is reduced by an approximate 100 mm.
- For pocket frames with internal opening (SI) of 52 or 55 mm, it is advisable to install a door panel with a max. thickness of 40 mm, including any frames for glass.
- To fasten the plasterboard sheets, use screws of max. 19 mm in correspondence with the reinforcement slats of the sheet.
- The use of 12.5 mm thick plasterboard sheets is recommended. • For special dimensions, please check the feasibility with the company.
- Standard payload of the supplied hanging kit: 150 Kg.