



DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY		MISURE DI INGOMBRO OVERALL DIMENSIONS		PANNELLO PORTA (LEGNO) DOOR PANEL (WOOD)				
L x H		Z x HT	P	LT	LP1	HP1	LP2	HP2
600 (300x2) x 2000/2100		1030 x 2100/2200	655	355	340	1990/2090	300	1987/2087
700 (350x2) x 2000/2100		1180 x 2100/2200	755	405	390	1990/2090	350	1987/2087
800 (400x2) x 2000/2100		1330 x 2100/2200	855	455	440	1990/2090	400	1987/2087
900 (450x2) x 2000/2100		1480 x 2100/2200	955	505	490	1990/2090	450	1987/2087
1000 (500x2) x 2000/2100		1630 x 2100/2200	1055	555	540	1990/2090	500	1987/2087
1100 (550x2) x 2000/2100		1780 x 2100/2200	1155	605	590	1990/2090	550	1987/2087
1200 (600x2) x 2000/2100		1930 x 2100/2200	1255	655	640	1990/2090	600	1987/2087

	PARETE FINITA - FINISHED WALL			
	90	105	125	150
H	2000/2100	2000/2100	2000/2100	2000/2100
SI	55	67	80	105
TR	60	80	100	120

NOTE TECNICHE - TECHNICAL NOTES

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm.
- La luce nominale (L) è ridotta di circa 50 mm.
- Per sede interna (SI) da 55 mm è consigliabile pannello porta con SP max 40 mm, comprese eventuali cornici fermavetro.
- Per misure speciali verificare fattibilità in azienda.
- Portata standard dei carrelli 150 Kg.
- Creation of pocket frames with height and width intervals every 50 mm.
- The doorway (L) is reduced by an approximate 50 mm.
- For pocket frames with internal opening (SI) of 55 mm, it is advisable to install a door panel with a max. thickness of 40 mm, including any frames for glass.
- For special dimensions, please check the feasibility with the company.
- Standard payload of the supplied hanging kit: 150 Kg.