



DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY	MISURE DI INGOMBRO OVERALL DIMENSIONS	P	LT	PANNELLO PORTA (LEGNO) DOOR PANEL (WOOD)	
				LP	HP
2400 x 2000/2030/2100	3730 x 2120/2150/2220	2450	640	615 ÷ 630	2010/2040/2110
2800 x 2000/2030/2100	4330 x 2120/2150/2220	2850	740	715 ÷ 730	2010/2040/2110
3200 x 2000/2030/2100	4930 x 2120/2150/2220	3250	840	815 ÷ 830	2010/2040/2110
3600 x 2000/2030/2100	5530 x 2120/2150/2220	3650	940	915 ÷ 930	2010/2040/2110
4000 x 2000/2030/2100	6130 x 2120/2150/2220	4050	1040	1015 ÷ 1030	2010/2040/2110
4400 x 2000/2030/2100	6730 x 2120/2150/2220	4450	1140	1115 ÷ 1130	2010/2040/2110
4800 x 2000/2030/2100	7330 x 2120/2150/2220	4850	1240	1215 ÷ 1230	2010/2040/2110

	PARETE FINITA - FINISHED WALL		
	150	174	200
H	500 ÷ 2300	500 ÷ 2700	500 ÷ 2700
SI	112	136	162
O	125	155	180

**NOTE TECNICHE - TECHNICAL NOTES**

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm. • La luce nominale (L) è ridotta di circa 50 mm.
- Per sede interna (SI) da 112 mm è consigliabile pannelli porta con SP max 40 mm, comprese eventuali cornici fermavetro. • Dimensioni disponibili a richiesta: L= 1200 mm ÷ 4800 mm e H= 500 ÷ 2700 mm. • Per il fissaggio delle lastre di cartongesso utilizzare viti L max 19 mm in corrispondenza delle doghe di rinforzo della lamiera. • Si consiglia l'utilizzo di lastre in cartongesso di 12,5 mm di spessore.
- Per misure speciali verificare fattibilità in azienda. • Portata standard dei carrelli 150 Kg.
- Creation of pocket frames with height and width intervals every 50 mm. • The doorway (L) is reduced by an approximate 50 mm.
- For pocket frames with internal opening (SI) of 112 mm, it is advisable to install a door panel with a max. thickness of 40 mm, including any frames for glass.
- Dimensions available on request: L= 1200 mm ÷ 4800 mm e H= 500 ÷ 2700 mm. • To fasten the plasterboard sheets, use screws of max. 19 mm in correspondence with the reinforcement slats of the sheet. • The use of 12.5 mm thick plasterboard sheets is recommended.
- For special dimensions, please check the feasibility with the company. • Standard payload of the supplied hanging kit 150 Kg.