



DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY		MISURE DI INGOMBRO OVERALL DIMENSIONS		PANNELLO PORTA (LEGNO) DOOR PANEL (WOOD)	
L x H		Z x HT		LP	HP
1200 x 2000/2030/2100		1930 x 2100/2130/2200		615 ÷ 630	2010/2040/2110
1400 x 2000/2030/2100		2230 x 2100/2130/2200		715 ÷ 730	2010/2040/2110
1600 x 2000/2030/2100		2530 x 2100/2130/2200		815 ÷ 830	2010/2040/2110
1800 x 2000/2030/2100		2830 x 2100/2130/2200		915 ÷ 930	2010/2040/2110
2000 x 2000/2030/2100		3130 x 2100/2130/2200		1015 ÷ 1030	2010/2040/2110
2200 x 2000/2030/2100		3430 x 2100/2130/2200		1115 ÷ 1130	2010/2040/2110
2400 x 2000/2030/2100		3730 x 2100/2130/2200		1215 ÷ 1230	2010/2040/2110

	PARETE FINITA - FINISHED WALL		
	150	174	200
H	500 ÷ 2300	500 ÷ 2700	500 ÷ 2700
SI	112	136	162
O	125	155	180

NOTE TECNICHE - TECHNICAL NOTES

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm. • La luce nominale (L) è ridotta di circa 25 mm.
- Per sedè interna (SI) da 112 mm è consigliabile pannelli porta con SP max 40 mm, comprese eventuali cornici fermavetro. • Dimensioni disponibili a richiesta: L= 600 mm ÷ 2400 mm e H= 500 ÷ 2700 mm. • Per il fissaggio delle lastre di cartongesso utilizzare viti L max 19 mm in corrispondenza delle doghe di rinforzo della lamiera.
- Si consiglia l'utilizzo di lastre in cartongesso di 12,5 mm di spessore. • Per misure speciali verificare fattibilità in azienda
- Portata standard dei carrelli 150 Kg.
- Creation of pocket frames with height and width intervals every 50 mm. • The doorway (L) is reduced by an approximate 25 mm.
- For pocket frames with internal opening (SI) of 112 mm, it is advisable to install a door panel with a max. thickness of 40 mm, including any frames for glass.
- Dimensions available on request: L= 600 ÷ 2400 mm e H= 500 ÷ 2700 mm. • To fasten the plasterboard sheets, use screws of max. 19 mm in correspondence with the reinforcement slats of the sheet. • The use of 12.5 mm thick plasterboard sheets is recommended.
- For special dimensions, please check the feasibility with the company. • Standard payload of the supplied hanging kit 150 Kg.