



DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY	MISURE DI INGOMBRO OVERALL DIMENSIONS		
L x H	Z x HT	P	LT
600 x 2000/2030/2100	1330 x 2100/2140/2200	655	635
700 x 2000/2030/2100	1530 x 2100/2140/2200	755	735
800 x 2000/2030/2100	1730 x 2100/2140/2200	855	835
900 x 2000/2030/2100	1930 x 2100/2140/2200	955	935
1000 x 2000/2030/2100	2130 x 2100/2140/2200	1055	1035
1100 x 2000/2030/2100	2330 x 2100/2140/2200	1155	1135
1200 x 2000/2030/2100	2530 x 2100/2140/2200	1255	1235

PANNELLO PORTA (LEGNO)
DOOR PANEL (WOOD)

LP	HP
615 ÷ 630	2010/2040/2110
715 ÷ 730	2010/2040/2110
815 ÷ 830	2010/2040/2110
915 ÷ 930	2010/2040/2110
1015 ÷ 1030	2010/2040/2110
1115 ÷ 1130	2010/2040/2110
1215 ÷ 1230	2010/2040/2110

PARETE FINITA - FINISHED WALL			
	150	174	200
H	500 ÷ 3000	500 ÷ 3000	500 ÷ 3000
SI	59	90	116
TR	120	-	-

NOTE TECNICHE - TECHNICAL NOTES

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm.
- Per sede interna (SI) da 59 mm è consigliabile pannello porta con SP max 44 mm, comprese eventuali cornici fermavetro.
- Dimensioni disponibili a richiesta: L=500 ÷ 1500 mm e H=500 ÷ 3000 mm.
- La dotazione standard comprende nr.2 scatole elettriche a 3 moduli (spessore 40 mm) e nr. 2 tubi corrugati premontati Ø 20 mm. È inoltre cablato nr.1 cavo di terra su ogni lato del controtelaio. Le predisposizioni per la posa di nr.3 tubi corrugati Ø 16/20/25 mm per le utenze elettriche sono presenti su entrambi i lati del controtelaio.
- Per misure speciali verificare fattibilità in azienda. • Portata standard dei carrelli 150 Kg.
- Creation of pocket frames with height and width intervals every 50 mm.
- For pocket frames with internal opening (SI) 59 mm, it is advisable to install a door panel with a max. thickness of 44 mm, including any frames for glass.
- Dimensions available on request: L=500 ÷ 1500 mm e H=500 ÷ 3000 mm.
- The system is supplied with n.2 socket boxes provided with 3 units (40 mm thick) and with n.2 premounted corrugated pipes Ø 20 mm. On each side of the frame there is n. 1 earthing wire. The settings for the electrical wiring and sockets of n.3 corrugated pipes Ø 16/20/25 mm are on both sides of the frame.
- For special dimensions, please check the feasibility with the company. • Standard payload of the supplied hanging kit: 150 Kg.