



DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY	MISURE DI INGOMBRO OVERALL DIMENSIONS			PANNELLO PORTA (LEGNO) DOOR PANEL (WOOD)			
		L x H	Z x HT	P	LT	LP	HP
1200 (600+600) x 2000/2030/2100	2530 x 2120/2160/2220			1250	635	615 ÷ 630	2010/2040/2110
1400 (700+700) x 2000/2030/2100	2930 x 2120/2160/2220			1450	735	715 ÷ 730	2010/2040/2110
1600 (800+800) x 2000/2030/2100	3330 x 2120/2160/2220			1650	835	815 ÷ 830	2010/2040/2110
1800 (900+900) x 2000/2030/2100	3730 x 2120/2160/2220			1850	935	915 ÷ 930	2010/2040/2110
2000 (1000+1000) x 2000/2030/2100	4130 x 2120/2160/2220			2050	1035	1015 ÷ 1030	2010/2040/2110
2200 (1100+1100) x 2000/2030/2100	4530 x 2120/2160/2220			2250	1135	1115 ÷ 1130	2010/2040/2110
2400 (1200+1200) x 2000/2030/2100	4930 x 2120/2160/2220			2450	1235	1215 ÷ 1230	2010/2040/2110

PARETE FINITA - FINISHED WALL			
	150	174	200
H	500 ÷ 3000	500 ÷ 3000	500 ÷ 3000
SI	59	90	116
TR	120	-	-

NOTE TECNICHE - TECHNICAL NOTES

- Realizzazione di controtelai con intervalli in altezza e larghezza ogni 50 mm.
- Per sede interna (SI) da 59 mm è consigliabile pannello porta con SP max 44 mm, comprese eventuali cornici fermavetro.
- Dimensioni disponibili a richiesta: L=500+500 ÷ 1500+1500 mm e H=500 ÷ 3000 mm.
- È possibile inserire fino a nr.3 tubi idraulici per lato con Ø max 25 mm compreso isolamento. Le predisposizioni idriche sono presenti su entrambi i lati di un controtelaio per la versione Type A, e su entrambi i controtelai per la versione Type B (da specificare in fase d'ordine).
- Per misure speciali verificare fattibilità in azienda. • Portata standard dei carrelli 150 Kg.
- Creation of pocket frames with height and width intervals every 50 mm.
- For pocket frames with internal opening (SI) 59 mm, it is advisable to install a door panel with a max. thickness of 44 mm, including any frames for glass.
- Dimensions available on request: L=500+500 ÷ 1500+1500 mm e H=500 ÷ 3000 mm.
- It is possible to host on each side of the frame up to nr. 3 plumbings with Ø max of 25 mm insulation included. The settings for the plumbing system are on both sides of one pocket frame for the Type A version, and on both pocket frames for the Type B version (to be specified when ordering).
- For special dimensions, please check the feasibility with the company. • Standard payload of the supplied hanging kit: 150 Kg.