



## DIMENSIONI STANDARD - STANDARD DIMENSIONS

LUCE DI PASSAGGIO DOORWAY		MISURE DI INGOMBRO OVERALL DIMENSIONS		DIMENSIONI PERSIANA/INFERRIATA THICKNESS OF SHUTTER/GRATING	
L	H	Z	HT	LP	HP
500 ÷ 1500	500 ÷ 2900	(L x 2) + 100	H + 120	L + 40	H + 10

DIMENSIONI - SPESORI DIMENSIONS - THICKNESSES		
SE	105	125
SI	67	87

ESEMPIO DI CALCOLO DEGLI INGOMBRI EXAMPLE OF CALCULATION OF THE OVERALL DIMENSIONS	
L = 900 mm	H = 2100 mm
APPLICARE LA FORMULA	APPLY THE FORMULA
Z = (900x2) + 100 = 1900 mm	
HT = 2100 + 120 = 2220 mm	

## NOTE TECNICHE - TECHNICAL NOTES

- Per altezze (H) superiori a 2400 mm è preferibile l'impiego del controtelaio con sede interna (SI) 87 mm.
- Per sede interna (SI) da 67 mm è preferibile l'impiego di persiane/inferriate di spessore max 50 mm.
- In caso di motorizzazione, il controtelaio dovrà essere maggiorato in larghezza (L) di 100 mm, altrimenti la luce di passaggio sarà ridotta di 100 mm.
- Fondo del controtelaio in alluminio.
- Per misure speciali verificare fattibilità in azienda.
- For heights (H) bigger than 2400 mm, it is advisable to use pocket frames with internal seat (SI) of 87 mm.
- For pocket frames with internal opening (SI) of 67mm, it is suitable for shutters/grating up to 50 mm thick.
- In case of motorisation, the pocket frame must be increased in width (L) by 100 mm, otherwise the doorway will be reduced by 100 mm.
- Pocket frame bottom in aluminium.
- For special dimensions, please check the feasibility with the company.